

# Product datasheet

Specifications



## photo-electric sensor - XUB - diffuse - Sn 0.1m - 12..24VDC - cable 5m

XUB4BNANL5

⚠ Discontinued

XUB4BNANL5 has not been replaced. Please contact your customer care centre for more information.

### Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor
Sensor name	XUB
Sensor design	Cylindrical M18
Detection system	Diffuse
Material	Metal
Line of sight type	Axial
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	3-wire
Discrete output type	NPN
Discrete output function	1 NO
Electrical connection	Cable
Cable length	5 m
Product specific application	-
Emission	Infrared diffuse
[Sn] nominal sensing distance	0.1 m diffuse

### Complementary

Enclosure material	Nickel plated brass
Lens material	PMMA
Maximum sensing distance	0.15 m diffuse
Output type	Solid state
Add on output	Without
Wire insulation material	PvR
Status LED	1 LED (yellow) for output state
[Us] rated supply voltage	12...24 V DC with reverse polarity protection

<b>Supply voltage limits</b>	10...36 V DC
<b>Switching capacity in mA</b>	<= 100 mA (overload and short-circuit protection)
<b>Switching frequency</b>	<= 500 Hz
<b>Maximum voltage drop</b>	<1.5 V (closed state)
<b>Current consumption</b>	35 mA no-load
<b>Maximum delay first up</b>	15 ms
<b>Maximum delay response</b>	1 ms
<b>Maximum delay recovery</b>	1 ms
<b>Setting-up</b>	Without sensitivity adjustment
<b>Diameter</b>	18 mm
<b>Length</b>	62 mm

## Environment

<b>Product certifications</b>	UL CE CSA
<b>Ambient air temperature for operation</b>	-25...55 °C
<b>Ambient air temperature for storage</b>	-40...70 °C
<b>Vibration resistance</b>	7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
<b>Shock resistance</b>	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
<b>IP degree of protection</b>	IP67 double insulation conforming to IEC 60529 IP65 double insulation conforming to IEC 60529

## Packing Units


<b>Package 1 Weight</b>	0.223 kg
<b>Package 1 Height</b>	1.300 dm
<b>Package 1 width</b>	0.660 dm
<b>Package 1 Length</b>	0.950 dm

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

**Dimensions**


---



**Wiring Schemes**

---


**NPN Outputs**



- BN :** Brown
- BU :** Blue
- BK :** Black

**Detection Curves**

---



- 1 : White 90%
- 2 : Grey 18%

Object 10 x 10 cm