



SIRIUS soft starter S0 32 A, 15 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC spring-type terminals

| General technical data | | |
|--|----|--------------------------|
| product brand name | | SIRIUS |
| product feature | | |
| <ul style="list-style-type: none"> integrated bypass contact system | | Yes |
| <ul style="list-style-type: none"> thyristors | | Yes |
| product function | | |
| <ul style="list-style-type: none"> intrinsic device protection | | No |
| <ul style="list-style-type: none"> motor overload protection | | No |
| <ul style="list-style-type: none"> evaluation of thermistor motor protection | | No |
| <ul style="list-style-type: none"> external reset | | No |
| <ul style="list-style-type: none"> adjustable current limitation | | No |
| <ul style="list-style-type: none"> inside-delta circuit | | No |
| product component motor brake output | | No |
| insulation voltage rated value | V | 600 |
| degree of pollution | | 3, acc. to IEC 60947-4-2 |
| reference code according to EN 61346-2 | | Q |
| reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750 | | G |
| Power Electronics | | |
| product designation | | Soft starter |
| operational current | | |
| <ul style="list-style-type: none"> at 40 °C rated value | A | 32 |
| <ul style="list-style-type: none"> at 50 °C rated value | A | 29 |
| <ul style="list-style-type: none"> at 60 °C rated value | A | 26 |
| yielded mechanical performance for 3-phase motors | | |
| <ul style="list-style-type: none"> at 230 V <ul style="list-style-type: none"> at standard circuit at 40 °C rated value | kW | 7.5 |
| <ul style="list-style-type: none"> at 400 V <ul style="list-style-type: none"> at standard circuit at 40 °C rated value | kW | 15 |
| yielded mechanical performance [hp] for 3-phase AC motor at 200/208 V at standard circuit at 50 °C rated value | hp | 7.5 |
| operating frequency rated value | Hz | 50 ... 60 |
| relative negative tolerance of the operating frequency | % | -10 |
| relative positive tolerance of the operating frequency | % | 10 |
| operating voltage at standard circuit rated value | V | 200 ... 480 |
| relative negative tolerance of the operating voltage at standard circuit | % | -15 |
| relative positive tolerance of the operating voltage at standard circuit | % | 10 |
| minimum load [%] | % | 10 |
| continuous operating current [% of I _e] at 40 °C | % | 115 |

| | | |
|--|----|--|
| power loss [W] at operational current at 40 °C during operation typical | W | 13 |
| Control circuit/ Control | | |
| type of voltage of the control supply voltage | | AC/DC |
| control supply voltage frequency 1 rated value | Hz | 50 |
| control supply voltage frequency 2 rated value | Hz | 60 |
| relative negative tolerance of the control supply voltage frequency | % | -10 |
| relative positive tolerance of the control supply voltage frequency | % | 10 |
| control supply voltage 1 at AC at 50 Hz | V | 110 ... 230 |
| control supply voltage 1 at AC at 60 Hz | V | 110 ... 230 |
| relative negative tolerance of the control supply voltage at AC at 50 Hz | % | -15 |
| relative positive tolerance of the control supply voltage at AC at 50 Hz | % | 10 |
| relative negative tolerance of the control supply voltage at AC at 60 Hz | % | -15 |
| relative positive tolerance of the control supply voltage at AC at 60 Hz | % | 10 |
| control supply voltage 1 at DC | V | 110 ... 230 |
| relative negative tolerance of the control supply voltage at DC | % | -15 |
| relative positive tolerance of the control supply voltage at DC | % | 10 |
| display version for fault signal | | red |
| Mechanical data | | |
| size of engine control device | | S0 |
| width | mm | 45 |
| height | mm | 150 |
| depth | mm | 150 |
| fastening method | | screw and snap-on mounting |
| mounting position | | With vertical mounting surface +/-10° rotatable, with vertical mounting surface +/- 10° tiltable to the front and back |
| required spacing with side-by-side mounting | | |
| • upwards | mm | 60 |
| • at the side | mm | 15 |
| • downwards | mm | 40 |
| wire length maximum | m | 300 |
| number of poles for main current circuit | | 3 |
| Connections/ Terminals | | |
| type of electrical connection | | |
| • for main current circuit | | spring-loaded terminals |
| • for auxiliary and control circuit | | spring-loaded terminals |
| number of NC contacts for auxiliary contacts | | 0 |
| number of NO contacts for auxiliary contacts | | 1 |
| number of CO contacts for auxiliary contacts | | 0 |
| type of connectable conductor cross-sections for main contacts for box terminal using the front clamping point | | |
| • solid | | 2x (1 ... 2.5 mm ²), 2x (2.5 ... 6 mm ²) |
| • finely stranded with core end processing | | 2x (1 ... 2.5 mm ²), 2x (2.5 ... 6 mm ²) |
| type of connectable conductor cross-sections for AWG cables for main contacts for box terminal | | |
| • using the front clamping point | | 1x 8, 2x (16 ... 10) |
| type of connectable conductor cross-sections for main contacts | | |
| • solid | | 1 ... 10 mm ² |
| • finely stranded with core end processing | | 1 ... 6 mm ² |
| type of connectable conductor cross-sections for auxiliary contacts | | |
| • solid | | 2x (0.25 ... 2.5 mm ²) |
| • finely stranded with core end processing | | 2x (0.25 ... 1.5 mm ²) |
| type of connectable conductor cross-sections for AWG cables | | |
| • for main contacts | | 16 ... 8 |

- for auxiliary contacts

2x (24 ... 14)

Ambient conditions

| | | |
|--|----|---|
| installation altitude at height above sea level | m | 5 000 |
| environmental category | | 2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m) 1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4 3K6 (no formation of ice, no condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6 |
| ambient temperature | | |
| • during operation | °C | -25 ... +60 |
| • during storage | °C | -40 ... +80 |
| derating temperature | °C | 40 |
| protection class IP on the front according to IEC 60529 | | IP20 |
| touch protection on the front according to IEC 60529 | | finger-safe, for vertical contact from the front |

Certificates/ approvals

General Product Approval

EMC



Confirmation



Declaration of Conformity

Test Certificates

other



Type Test Certificates/Test Report

Confirmation Miscellaneous

UL/CSA ratings

| | | |
|---|----|-------------|
| yielded mechanical performance [hp] for 3-phase AC motor | | |
| • at 220/230 V | | |
| — at standard circuit at 50 °C rated value | hp | 7.5 |
| • at 460/480 V | | |
| — at standard circuit at 50 °C rated value | hp | 20 |
| contact rating of auxiliary contacts according to UL | | B300 / R300 |

